



8 Port Gigabit Power over Ethernet Midspan POE125U for 10/100/1000 Base-T Networks



Features

- IEEE802.3at Pre-Standard
- Low Cost
- Gigabit Compatible
- Optional Mounting Kit for 19" Rack
- Optional SNMPv3 with TLS/SSL
- Full Power of 125W – 15.4W per port
- No Power Management Required
- Full Protection OTP, OCP, OVP
- 1 Year Warranty
- Optional Cisco Legacy Detection

Applications

- VoIP Phones
- Access Points
- Security Systems
- IP Cameras

Safety Approvals

- cUL/UL
- CE

Mechanical Characteristics

- Length: 224.9mm (8.85in)
- Width: 200mm (7.87in)
- Height: 48.5 mm (1.91in)
- Weight: 1.4Kg (3.0lbs)

Output Specifications

Model	Number of Ports	Cisco Legacy Support	SNMP
POE125U-8-C	8	Yes	No
POE125U-8-N	8	Yes	Yes

Optional 19" Rack mounting adapter to mount 1 POE125U or 2 side by side; order P/N POE125U-ACCY01

Reference files:

1. [Phihong Midspan PoE GUI User Manual-v1.0.pdf](#)
2. [Phihong Midspan PoE GUI Installation v1.0.exe](#)
3. [PL2303 Prolific DriverInstaller v1_12_0.zip](#)
4. [POE125U Series Firmware-Rev2.5.zip](#)
5. [Multiport Midspan Installation Manual.pdf](#)
6. [19in Rack Mounting Kit Datasheet.pdf](#)
7. [SNMPv2c User Manual-Rev1.7.pdf](#)
8. [SNMPv2c Firmware-Rev1.7.zip](#)
9. [SNMPv2c MIB_10_30_2009.zip](#)

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:**AC Input Voltage Range**

90 to 264VAC

Input Voltage Rating

100 to 240VAC

Input Frequency

47 to 63Hz

Input Current

2.5A (RMS) max for 90VAC

1.3A (RMS) max for 230 AC

Leakage Current

<3.5mA max at 254VAC, 60Hz

AC Inrush Current

30A (RMS) max for 115VAC

60A (RMS) max for 230VAC

OUTPUT:**Total Output Power**

15.4W per port, 125W Total Power

Ripple and Regulation

100mV maximum

Efficiency

75% (typical at maximum load, and 120V

AC 60Hz

Hold-up Time

10mS minimum 120VAC max load

Transient O/P Voltage Protection

60V maximum at switch on and off at any

AC line phase

Turn-On Delay Time

3 sec max at max load,120VAC 60Hz, 25Hz

ENVIRONMENTAL:**Temperature**

Operation 0°C to +40°C

Non-operation -25°C to +65°C

Humidity 5% to 90%

EMI

Complies with FCC Class B

Complies with EN55032 Class B

Immunity

ESD: EN61000-4-2 Level 3

RS: EN61000-4-3 Level 2

EFT: EN61000-4-4 Level 2

Surge: EN61000-4-5 Level 3

CS: EN61000-4-6 Level 2

Voltage Dips: EN61000-4-11

Harmonic: EN61000-3-2 Class A

IEEE802.3af Interoperability

UNH Interoperability report available upon request

FEATURES:**Cisco Legacy Detection (Option)**

No extern parts required for Legacy devices:

VoIP Phones: 7910,7912,7940,7960

Access Points: 350,1100,1200

Over Voltage/Current, Short Circuit Protection

Outputs equipped with short circuit protection and overload protection as per 802.3af specification. The output can be shorted permanently without damage

Over Temperature Protection

Automat shutdown without damage

Indicators

Green LED: Power detected "ON"

Yellow LED: Fault Detected

Input Connector

AC Input IEC320 3 Pin

